

DSLR CAMERA KIT

- Enable 24.2MP CMOS sensor
- DIGIC6 processor
- Finder penta mirror. Field of view 95%, magnification 0.82 times, the eye point 19mm
- AF 19-point cross-type. Center F2.8 corresponding dual cross
- 7560-pixel RGB-IR photometry sensor. 63 zone TTL metering
- ISO100-12800 (extended with 25600)
- The shutter speed is 30 seconds -1/4000 seconds (Synchro 1/200 sec)
- Continuous shooting 5 frames / sec.
- LCD monitor 3 inches 1.04 million dots. Vari-Angle
- Built-in guide number 12 flash
- New hybrid CMOS AF III
- Video Full HD 30fps
- Wi-Fi · NFC
- Remote operation by computer
- 2 pcs. Battery LP-E17
- The size of 131.9 x 100.7 x 77.8mm
- Weight 555g (CPA criteria). 510g (body only)
- EF-S 18-135mm f/3.5-5.6 IS STM lens
- Battery charger for LP-E17 battery
- Memory card 64 GB
- Carrying Bag (back pack)
- Flashguns
- Angle wall bracket
- USB cord

ELETRONIC DOOR LOCK

Access solutions

- No. of credentials up to 78 pin codes
- Register card up to 30 cards
- Pin code must create 8 digits
- Mechanical keys: 3

Features

- Easy to install and can replace with knob
- Yale YDME50 has various access solutions, Card, Pin code, Key override for your convenience
- Modem design and Invisible keypad which can be seen only when you touch the screen with your palm
- Automatic Locking
- Emergency Power
- 3-minute Lock Out Feature
- Key Override
- Passage Mode

Arnold B. Gonzales
3/21/19