

Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Quantity	Total	Delivered, Weeks/Months
1	Video Conference System with Rally Camera	Set(s)	3	Within Forty-Five (45) Calendar days from conforme of Purchase Order.
2	Speaker Bar	Unit(s)	6	Within Forty-Five (45) Calendar days from conforme of Purchase Order
3	Mic Pods	Unit(s)	6	Within Forty-Five (45) Calendar days from conforme of Purchase Order
4	Remote	Unit(s)	3	Within Forty-Five (45) Calendar days from conforme of Purchase Order.
5	Mounting Kit	Unit(s)	3	Within Forty-Five (45) Calendar days from conforme of Purchase Order.
TOTAL		Unit (s)	21	Three (3) set(s) Video Conference Equipment

Technical Specifications

2

Technical Specifications

ITEM	MINIMUM SPECIFICATION	INDICATE "COMPLY" OR "NOT COMPLY
CAMERA	<ul style="list-style-type: none"> • Resolution: Up to 4K Ultra HD at 30 fps 	
	<ul style="list-style-type: none"> • Pan, Tilt, Zoom: $\pm 90^\circ$ pan, $+50^\circ / -90^\circ$ tilt, 15x HD zoom (5x optical, 3x digital) 	
	<ul style="list-style-type: none"> • Field of View: 90° diagonal, 82.1° horizontal, 52.2° vertical 	
	<ul style="list-style-type: none"> • Technologies: RightLight™ for optimal lighting, RightSight™ for automatic participant framing 	
	<ul style="list-style-type: none"> • Additional Features: Autofocus, 3 camera presets, Kensington security slot, video mute/unmute LED indicator, lens parks at -90° in sleep mode for privacy 	
	<ul style="list-style-type: none"> • Dimensions: Height: 182.5 mm, Width: 152 mm, Depth: 152 mm 	
	<ul style="list-style-type: none"> • Weight: 1513 g 	
MICROPHONE PODS	<ul style="list-style-type: none"> • Pickup Range: 15 ft / 4.5m diameter 	
	<ul style="list-style-type: none"> • Microphones: Four omnidirectional microphones forming eight acoustic beams 	
	<ul style="list-style-type: none"> • Technologies: Acoustic Echo Cancellation (AEC), Voice Activity Detector (VAD), background noise suppression 	
	<ul style="list-style-type: none"> • Additional Features: Mute button with LED status indicator, daisy chain up to 7 mic pods 	
	<ul style="list-style-type: none"> • Frequency Response: 90Hz – 16kHz 	
	<ul style="list-style-type: none"> • Sensitivity: $>-27\text{dB} \pm 1\text{dB} @ 1\text{Pa}$ 	
	<ul style="list-style-type: none"> • Dimensions: Height: 21 mm, Width: 102 mm, Depth: 102 mm 	
	<ul style="list-style-type: none"> • Weight: 296 g 	
SPEAKERS	<ul style="list-style-type: none"> • Driver: High-performance 3" (76mm) driver with rare-earth magnet 	
	<ul style="list-style-type: none"> • Technologies: Patent-pending suspension system to eliminate vibration-induced camera shake and audio interference 	
	<ul style="list-style-type: none"> • Volume: 95dB SPL @1W, 100dB SPL @7.5W, both $\pm 2\text{dB}$ at $\frac{1}{2}$ meter 	
	<ul style="list-style-type: none"> • Sensitivity: $95 \pm 2\text{dB SPL}$ at $\frac{1}{2}$ meter 	
	<ul style="list-style-type: none"> • Distortion: 200Hz–300Hz $< 2.5\%$, 300Hz–10kHz $< 1\%$ @7.5W 	
	<ul style="list-style-type: none"> • Dimensions: Height: 103 mm, Width: 449 mm, Depth: 80 mm 	
	<ul style="list-style-type: none"> • Weight: 1645 g 	

2

HUBS	Driver: High-performance 3" (76mm) driver with rare-earth magnet	
	Technologies: Patent-pending suspension system to eliminate vibration-induced camera shake and audio interference	
	Volume: 95dB SPL @1W, 100dB SPL @7.5W, both +/-2dB at ½ meter	
	Sensitivity: 95+/-2dB SPL at ½ meter	
	Distortion: 200Hz–300Hz < 2.5%, 300Hz–10kHz < 1% @7.5W	
	Dimensions: Height: 103 mm, Width: 449 mm, Depth: 80 mm	
CONNECTIVITY AND COMPATIBILITY	Wireless Protocol: Remote control BLE	
	Wired Network Support: N/A	
	Software Support: Proposed brand sync app	
	Operating Systems: Windows 10 and Windows 11, Mac 10.10 or higher, Chrome OS	
	System Requirements: Resolutions higher than 1080p require Windows 10 or higher, macOS 10.10 or higher, USB 3.0 port and Type C cable	
ADDITIONAL FEATURES	RightSound Technologies: Machine learning AI to distinguish human speech from other sounds, auto-level loud and soft voices, very low distortion broadside beamforming algorithm	
	RightLight Technologies: Wide Dynamic Range (WDR), low-light compensation, video noise reduction, low-light saturation optimization	
	RightSight Technologies: Human figure detection, auto-frame participants at meeting start, auto-frame participants on-demand, auto-reframe participants during meetings	

PENALTY

The winning bidder/supplier must complete the delivery or performance as per the agreed Work Plan. If they fail to deliver on time or only partially complete the work, CIAC will impose a Delay Penalty of 0.1% of the cost of the undelivered portion per day of delay until completion. This penalty applies if the final acceptance date is missed. For delays due to unavoidable circumstances (e.g., natural disasters), the bidder/supplier must submit a report detailing the delay, impacted deliverables, and a catch-up plan for CIAC's approval.